

# Fabricated Manhole Connectors and Sewer Junctions

A range of non-pressure manhole connectors and sewer junctions to suit local authority specifications.



TECHNICAL GUIDE: **PF10.1**

## Applications

Sewer connections into concrete manholes

## Product Attributes

Quality fabrication  
Range of sizes and configurations to suit different applications  
Can be customised to suit specific requirements  
High stiffness rating of SN16

## Approvals/Standards

Approved patents 329263, 328354, 227686

## Quality

ISO 9001:2008 Quality Management Standard

A range of non-pressure sewer junctions to suit local authority specifications. Product development expertise is available to customise your requirements.

| Figure No. | Code          | Description   |
|------------|---------------|---|
| 1          | CON100H       | Manhole starter 100mm PVC/EW                          |
| 2          | CON150H       | Manhole starter 150mm PVC/EW                          |
| 3          | 1504.150100L  | Lunden junction SN16 collar/spigot 150 x 100 x 88°    |
| 4          | 1505.150100LC | Lunden junction SN16 double collar 150 x 100 x 88°    |
| 5          | 1504.150100LS | Lunden junction SN16 double spigot                    |
| 6          | 1506.100DGM   | Manukau drop junction SN16 100 x 88°                  |
| 7          | 1506.150DGM   | Manukau drop junction SN16 150 x 88°                  |
| 8          | 1500.100.600G | Manhole gritted short SN16 100 x 600                  |
| 9          | 1500.150.600G | Manhole gritted short SN16 150 x 600                  |
| 10         | 1504.150100DS | 45° Sewer junction SN16 double spigot 150 x 100 x 45° |
| 11         | 1504.150100DC | 45° Sewer junction SN16 double collar 150 x 100 x 45° |
| 12         | 1504.150100SC | 45° Sewer junction SN16 collar/spigot 150 x 100 x 45° |



**FIG. 1** Manhole starter 100mm PVC/EW



**FIG. 2** Manhole starter 150mm PVC/EW



**FIG. 3** Lunden junction SN16 collar/spigot 150 x 100 x 88°



**FIG. 4** Lunden junction SN16 double collar 150 x 100 x 88°



**FIG. 5** Lunden junction SN16 double spigot



**FIG. 6** Manukau drop junction SN16 100 x 88°



**FIG. 7** Manukau drop junction SN16 150 x 88°



**FIG. 8** Manhole gritted short SN16 100 x 600



**FIG. 9** Manhole gritted short SN16 150 x 600



**FIG. 10** 45° Sewer junction SN16 double spigot 150 x 100 x 45°



**FIG. 11** 45° Sewer junction SN16 double collar 150 x 100 x 45°



**FIG. 12** 45° Sewer junction SN16 collar/spigot 150 x 100 x 45°



Scan for more  
information

**Disclaimer:** While every effort has been made to ensure that the information in this document is correct and accurate, users of Hygrade Water product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hygrade Water unless expressly stated in any sale and purchase agreement entered into between Hygrade Water and the user.

**September 2023**

**0800 494 723**  
**hygradewater.co.nz**

**102 Neilson Street**  
Onehunga, Auckland 1061, New Zealand  
PO Box 58 142, Botany, Auckland 2163

